

Autex Insulation Data Sheet



Quality 100% Polyester Thermal Insulation for Ceilings, Walls, Between Floors and Underfloors

GreenStuf® is a thermally bonded insulation manufactured from 100% polyester fibre. There are no additives or other components used in the process. GreenStuf® insulation is non-irritant, user-friendly, thermally efficient polyester insulation for residential and commercial applications.

GreenStuf® is supplied as a lofted green tinted insulation product.



Features and Benefits

- User-friendly - no protective clothing required
- Non-irritant, non-toxic, non-allergenic
- Fire safe - fully complies with the Building Code of Australia (BCA)
- Easy installation - can be torn straight across its width
- Long term stability and performance, 50+ years rating
- Available in a range of thermal values
- Excellent acoustic properties

Applications

- GreenStuf® is designed for use as a safe and efficient thermal insulation for residential and commercial buildings.
 - Ceilings
 - External Walls
 - Between Floors
 - Underfloor

Product (R Value)	Nominal Thickness (mm)	Width (mm)	Batts per Pack	m ² per Pack	Coverage per Pack (m ²)
GreenStuf® R1.5	100	430	16	8.0	9.2
GreenStuf® R1.5	100	580	16	10.8	12.4
GreenStuf® R2.0	120	430	12	6.0	6.9
GreenStuf® R2.0	120	580	12	8.1	9.3
GreenStuf® R2.5	155	430	8	4.0	4.6
GreenStuf® R2.5	155	580	8	5.4	6.2
GreenStuf® R3.0	170	430	8	4.0	4.6
GreenStuf® R3.0	170	580	8	5.4	6.2
GreenStuf® R3.5	190	430	8	4.0	4.6
GreenStuf® R3.5	190	580	8	5.4	6.2

NB: Batt length = 1160mm. Coverage is nominal and will vary due to types of framing.

